

MITANOL X-Force 5W-40 RSi

HC-synthetic high-performance low viscosity engine oil for passenger cars

Properties

MITANOL X-Force 5W-40 RSi is a synthetic high-performance fuel-efficient engine oil of the SAE class 5W-40. Synthetic components and an innovative additive system tailored thereto ensure compliance with current practical requirements. The significantly improved engine oil quality of **MITANOL X-Force 5W-40 RSi** is especially reflected in the further improved wear protection and the improved engine cleanliness, even with extended oil change intervals. The extremely low low-temperature viscosity combined with a safe high-temperature viscosity ensures a high fuel-saving potential.

Application notes

MITANOL X-Force 5W-40 RSi is suitable as a high-performance, low viscosity engine oil for demanding engines. Recommended for passenger car petrol and diesel engines, including turbo versions and for direct injection engines, under all operating conditions.

Service description

Specifications:

- ACEA A3/B4
- API SN/CF

Recommendation*:

- BMW Longlife -01
- MB 226.5
- MB 229.5
- Opel GM-LL-B-025
- Porsche A 40
- PSA B71 2296
- Renault RN0700/ RN0710
- VW 502 00/ 505 00

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL X-Force 5W-40 RSi
Density at 15°C	DIN 51 757	kg/m ³	856
Viscosity 100°C	DIN 51 562	mm ² /s	14.31
Viscosity index (VI)	DIN ISO 2909	-	174
Viscosity at -30°C	DIN 51 377	mPa.s	6030
Pour point	DIN ISO 3016	°C	-36
Flash point COC	DIN ISO 2592	°C	224
TBN	DIN ISO 3771	mg KOH/g	10.2

* meets the requirements of the OEM manufacturer.
 The stated values may vary within the usual commercial range.